

-40°C Freezer



268L

328L

528L

Technical Parameters

Model	BDF-40V268	BDF-40V328	BDF-40V528
External Size(W*D*H)	673*676*1630mm	673*676*1860mm	900*819*1828mm
Internal Size(W*D*H)	508*455*1137mm	508*455*1393mm	651*631*635mm 651*631*635mm
Capacity	268L	328L	528L
Type	Vertical		
Temp. Range	-30°C~-40°C		-20~-40°C
Temp. Accuracy	0.1°C		
Control System	Microprocessor Control LED Display		
Alarm	High or low temperature alarm,power failure alarm,door ajar alarm,sensor failure alarm (only for BDF-40V268&BDF-40V328),temperature controllers failure alarm		
Refrigeration Type	Direct Refrigeration		
Refrigerant	R290		Mixed refrigerant
Compressor	Unicompressor,imported famous brand compressor		
Structure	Uniboday design		
Material	Internal	Color sprayed steel	Painted steel panel
	External	Color sprayed steel	Painted steel panel, 95mm foaming insulation
Drawer/Shelf	3pcs shelves	3pcs shelves	18 drawers
Consumption	300W		345W
Power Supply	AC220V±10%, 50/60HZ; 110V, 60Hz		
Package Size	760*770*1800mm	770*770*2040mm	930*970*2000mm
Gross Weight	115kg	131kg	184kg



268L/362L



398L

Technical Parameters

Model	BDF-40V268II	BDF-40V362	BDF-40V398
External Size(W*D*H)	690*744*1631mm	690*744*1885mm	850*960*1860mm
Internal Size(W*D*H)	520*567*1013mm	520*567*1266mm	550*630*1140mm
Capacity	268L	362L	398L
Type	Vertical		
Temp. Range	-30°C~-40°C		-15~-40°C
Temp. Accuracy	0.1°C		
Control System	Microprocessor Control; Digital Display		
Alarm	High or low temperature alarm,door ajar alarm,power failure alarm,temperature controller failure alarm		High or low temperature alarm, sensor failure alarm
Refrigeration Type	Direct Refrigeration		
Refrigerant	Mixed refrigerant		
Compressor	Unicompressor,imported famous brand compressor		
Construction	Structure	Uniboday design	
	Internal Material	Stainless steel	
	External Material	Painted steel panel,110mm foaming insulation	Painted steel panel,150mm foaming insulation
	Drawer/Shelf	4pcs shelves,Stainless Steel	5pcs shelves,Stainless Steel
Consumption	335W	360W	550W
Power Supply	AC220V±10%,50/60HZ;110V,60Hz		
Package Size	810*860*1820mm	810*860*2100mm	935*1030*2030mm
Gross Weight	165kg	180kg	250kg